

LINE 2

BOOK CV-2030 1966 G. SANDUL

219 - RIB LAKE

BM 41 SAN 1966 0 0 03.6 478.517 M 1569.933 FT
 BM, OGEMA, 3.5 MI N. AND 2.25 MI E. OF; APPROX. NEAR N. SIXTEENTH COR. BETWEEN SECS. 28 AND 29, T. 35 N., R. 2 E.; ON CO. HWY. "C", AT SMALL CONCRETE BRIDGE OVER MONDEAUX CREEK; 12 FT NORMAL AND ON N. SIDE OF RD.; 0.5 FT LOWER THAN CENTER OF BRIDGE; 6.8 FT ABOVE WATER LEVEL; SET IN THE TOP OF NW. CONCRETE WINGWALL; STANDARD TABLET STAMPED "41 SAN 1966 1570"

BM 20 FWK 1962 0 0 06.4 504.378 M 1654.780 FT
 BM, OGEMA, 0.6 MI N. AND 2.2 MI E. OF; T. 34 N., R. 2 E., NEAR COR. SECS. 4, 5, 8 AND 9; ALONG THE N. RIGHT-OF-WAY OF STATE HWY. 86; 50 FT N. AND 23 FT E. OF CENTER OF HWY. AT T-RD. N.; 16 FT N. AND 26 FT W. OF TELEPHONE POLE; 3 FT S. AND 10 FT E. OF A TRIANGULAR BLAZED 6 IN. BIRCH TREE; 4.9 FT HIGHER THAN HWY.; 33.8 FT HIGHER THAN T-RD. N., IN A CONCRETE POST; A STANDARD TABLET STAMPED "20 FWK 1962 1654" AND MARKED WITH A STANDARD "BM" TAG

LINE 3

BOOK CV-1470 1962 F. W. KRUEGER

218 - RIB LAKE

UE 1806 0 0 07.7 550.546 M 1806.250 FT
 UE, 0.5 MI E. (ACROSS COUNTRY) FROM OGEMA TOWER 1934; T. 34 N., R. 2 E., NEAR COR. SECS. 1, 2, 11 AND 12; 5 FT S. AND 20 FT E. OF STATE HWY. 86, AT A T-RD. NW., ON A 5 FT GRANITE BOULDER; 0.3 FT HIGHER THAN T-RD.; A CHISELED SQUARE

UE PEARSON HILL 1962 RM 0 0 09.3 594.584 M 1950.730 FT
 REFERENCE MARK, 1 FT N. OF TABLET; TOP OF BULL HEAD SET IN A 2.5 X 2.5 IN. CONCRETE POST; A CHISELED CROSS; POSSIBLY SET BY THE WISCONSIN STATE HWY. COMMISSION (NOT PAINTED) (ELEV. BY STATE HWY. COMM.)

BM PEARSON HILL 1962 0 0 09.3 594.597 M 1950.774 FT
 BM, OGEMA, 4.4 MI E. OF; T. 34 N., R. 2 E., IN THE SW 1/4 SEC. 12; MARK IS LOCATED ON THE HIGHEST POINT OF A RIDGE COVERED WITH FIRST, SECOND AND THIRD GROWTH MAPLE TREES, THE RIDGE IS KNOWN LOCALLY AS PEARSON HILL. THE HILL MAY BE REACHED FROM STATE HWY. 86 BY TRAVELING S. ON A PRIVATE LANE LEADING TO THE SWANSON FARM KNOWN AS SUGAR BUSH HILL FOR APPROX. 0.5 MI, THENCE SW. FOR 0.2 MI TO THE FARM, PROCEED NNE. THROUGH THE WOODS TO THE TOP OF THE HILL AND THE MARK; THE MARK IS 6 FT N. AND 5 FT E. OF A 32 IN. MAPLE TREE, 1 FT S. OF A 2 X 2 IN. CONCRETE MARKER WITH A CHISELED BULL SET BY THE WISCONSIN STATE HWY. COMMISSION, IN CONCRETE POST; A STANDARD TABLET STAMPED "PEARSON HILL 1962 1950.447" AND TAGGED WITH A STANDARD BM MARKER. (ELEV. BY USGS)

LINE 4

BOOK CV-1470 1962 F. W. KRUEGER

218 - RIB LAKE

BM OGEMA TOWER 1934 0 0 00.4 595.335 M 1953.195 FT
 BM, NGS TRIANGULATION STATION OGEMA, ABOUT 5 MI E. OF; IN NW 1/4 NW 1/4 SEC. 11, T. 34 N., R. 2 E., ON WOODEN PROMINENT KNOWN LOCALLY AS TIMMS HILL, CENTER UNDER 84 FT STEEL TOWER, IN CONCRETE POST; STANDARD TABLET STAMPED "OGEMA TOWER 1934 1952.868" THIS MARK PRO-

LINE 1

BOOK CV-2004 1970 D. W. BENNETT

216 - RID LAKE

BM 14 DNB 1970 1 60 07.1 478.485 M 1569.828 FT
 BM, JCT. U.S. HWYS. 8 AND 51; 16.3 MI W. ALONG U.S. HWY. 8, THENCE 4 MI S. ALONG CO. TRUNK HWY. "YY" FROM, ON THE LINCOLN PRICE CO. LINE; T. 35 N., RS. 3 AND 4 E., NEAR COR. SECS. 19, 24, 25 AND 30; 165 FT S., 81 FT E. AND 3.8 FT HIGHER THAN JCT. OF CO. TRUNK HWY. "YY", LOST AVENUE W., SQUAM CREEK RD. E.; 73 FT N. OF NW. CORNER OF SMALL WHITE HOUSE; 73 FT NE. OF POWER POLE; 31 FT N. OF A DRIVE; 1 FT N. OF A YELLOW WOODEN RIGHT-OF-WAY POST; 1 FT S. OF A WITNESS SIGN; STANDARD TABLET SET ON 15 FT OF DRIVEN COPPER COATED ROD IN A 6 IN. GRAVEL FILLED METAL PIPE COLLAR; STAMPED "14 DNB 1970"

UE 14 B 1 62 08.7 463.907 M 1522.000 FT
 UE, 1.6 MI S. ALONG CO. TRUNK HWY. "YY" FROM TABLET; TPS. 34 AND 35 N., RS. 3 AND 4 E., ABOUT 1800 FT N. OF COR. SECS. 1, 6, 31 AND 36; AT A DOUBLE 5 X 12 FT CONCRETE BOX CULVERT FOR RITCHIE CREEK; CHISELED "X" ON N. END OF W. HEADWALL, 30 FT W. AND 2.7 FT LOWER THAN RD., 4 FT ABOVE WATER

UE 15 DNB 1970 RM 1 63 09.8 470.042 M 1542.130 FT
 REFERENCE MARK, 100 FT NW. OF MARK, ON TOP OF NW. WINGWALL; CHISELED "X"

BM 15 DNB 1970 1 64 09.8 469.777 M 1541.261 FT
 BM, TOMAHAWK, 17 MI W. ALONG WISCONSIN STATE HWY. 86; THENCE 0.7 MI N. ALONG CO. TRUNK HWY. "YY" FROM JCT. U.S. HWY. 51 AND WISCONSIN HWY. 86 AT; T. 34 N., RS. 3 AND 4 E., ABOUT 0.2 MI N. OF COR. SECS. 1, 6, 7 AND 12; AT THE HWY. "YY" BRIDGE OVER N. FORK SPIRIT RIVER; 51 FT SE. OF AND 0.1 FT HIGHER THAN CENTER OF BRIDGE; 17 FT E. OF CENTER OF, 2 FT SE. OF END OF E. BRIDGE RAIL; 12.5 FT ABOVE WATER; STANDARD TABLET SET IN DRILL HOLE IN TOP OF SE. WINGWALL; STAMPED "15 DNB 1970"

UE 15 A 1 65 10.1 469.347 M 1539.850 FT
 UE, 0.2 MI S. AND 0.1 MI E. OF TABLET; T. 34 N., RS. 3 AND 4 E., ABOUT 0.1 MI E. OF COR. SECS. 1, 6, 7 AND 12; AT A CONCRETE BRIDGE OVER N. FORK SPIRIT RIVER; 13 FT N. AND 0.2 FT LOWER THAN CENTER OF BRIDGE; CHISELED "X" ON W. ABUTMENT

BM FF 1 67 12.5 456.850 M 1498.850 FT
 BM, TOMAHAWK, 14.7 MI W. ALONG STATE HWY. 86 FROM JCT. U.S. HWY. 51 AND STATE HWY. 86 AT; T. 34 N., R. 4 E., NEAR COR. SECS. 4, 5, 6 AND 9; 26 FT S., 18 FT W. AND 0.7 FT LOWER THAN HWY. 86 AND OLD RD. S., 36 FT W. OF WISCONSIN HWY. DEPT. REF. POINT SIGN (86 E 37); 54 FT SSE. OF A "DO NOT PASS" SIGN, A 4 X 4 IN. CONCRETE POST WITH METAL CAP AND LETTERS BM IN SIDE (ELEV. BY USGS); THIS BM IS DESIGNATED AS "FF" BY WISCONSIN VALLEY IMPROVEMENT CO.

217 - SPIRIT FALLS

BM SPIRIT NO 2 1952 RM 1 68 12.8 463.860 M 1521.846 FT
 REFERENCE MARK 2, IS A STANDARD DISK SET IN A CONCRETE MONUMENT THAT PROJECTS 6 IN. AND IS 13 FT W. OF THE CENTER OF A GRAVEL RD., 114 FT NW. OF STATION

LINE 2

BOOK CV-2030 1966 G. SANDUL

219 - RIB LAKE

BM 41 SAN 1966 0 0 03.6 478.517 M 1569.933 FI
 BM, OGEMA, 3.5 MI N. AND 2.25 MI E. OF; APPROX. NEAR N. SIXTEENTH COR.
 BETWEEN SECS. 28 AND 29, T. 35 N., R. 2 E.; ON CO. HWY. "C", AT SMALL
 CONCRETE BRIDGE OVER MONDEAUX CREEK; 12 FT NORMAL AND ON W. SIDE OF
 RD.; 0.5 FT LOWER THAN CENTER OF BRIDGE; 6.8 FT ABOVE WATER LEVEL; SET
 IN THE TOP OF NW. CONCRETE WINGWALL; STANDARD TABLET STAMPED "41 SAN
 1966 1570"

BM 20 FWK 1962 0 0 06.4 504.378 M 1654.780 FI
 BM, OGEMA, 0.6 MI N. AND 2.2 MI E. OF; T. 34 N., R. 2 E., NEAR COR.
 SECS. 4, 5, 8 AND 9; ALONG THE N. RIGHT-OF-WAY OF STATE HWY. 86; 50 FT
 N. AND 623 FT E. OF CENTER OF HWY. AT T-RD. N.; 16 FT N. AND 26 FT W.
 OF TELEPHONE POLE; 3 FT S. AND 10 FT E. OF A TRIANGULAR BLAZED 6 IN.
 BIRCH TREE; 4.9 FT HIGHER THAN HWY.; 53.8 FT HIGHER THAN T-RD. N., IN
 A CONCRETE POST; A STANDARD TABLET STAMPED "20 FWK 1962 1654" AND
 MARKED WITH A STANDARD "BM" TAG

LINE 3

BOOK CV-1470 1962 F. W. KRUEGER

218 - RIB LAKE

UE 1806 0 0 07.7 550.546 M 1806.250 FI
 UE, 0.5 MI E. (ACROSS COUNTRY) FROM OGEMA TOWER 1934; T. 34 N., R. 2
 E., NEAR COR. SECS. 1, 2, 11 AND 12; 5 FT S. AND 20 FT E. OF STATE
 HWY. 86, AT A T-RD. NW., ON A 5 FT GRANITE BOULDER; 0.3 FT HIGHER THAN
 T-RD.; A CHISELED SQUARE

UE PEARSON HILL 1962 RM 0 0 09.3 594.584 M 1950.730 FI
 REFERENCE MARK, 1 FT N. OF TABLET; TOP OF BULL HEAD SET IN A 2.5 X
 2.5 IN. CONCRETE POST; A CHISELED CROSS; POSSIBLY SET BY THE WISCONSIN
 STATE HWY. COMMISSION (NOT PAINTED) (ELEV. BY STATE HWY. COMM.)

BM PEARSON HILL 1962 0 0 09.3 594.597 M 1950.774 FI
 BM, OGEMA, 4.4 MI E. OF; T. 34 N., R. 2 E., IN THE SW 1/4 SEC. 12;
 MARK IS LOCATED ON THE HIGHEST POINT OF A RIDGE COVERED WITH FIRST,
 SECOND AND THIRD GROWTH MAPLE TREES, THE RIDGE IS KNOWN LOCALLY AS
 PEARSON HILL. THE HILL MAY BE REACHED FROM STATE HWY. 86 BY TRAVELING
 S. ON A PRIVATE LANE LEADING TO THE SWANSON FARM KNOWN AS SUGAR BUSH
 HILL FOR APPROX. 0.5 MI, THENCE SW. FOR 0.2 MI TO THE FARM, PROCEED
 NNE. THROUGH THE WOODS TO THE TOP OF THE HILL AND THE MARK; THE MARK
 IS 6 FT N. AND 5 FT E. OF A 32 IN. MAPLE TREE, 1 FT S. OF A 2 X 2 IN.
 CONCRETE MARKER WITH A CHISELED BULL SET BY THE WISCONSIN STATE HWY.
 COMMISSION, IN CONCRETE POST; A STANDARD TABLET STAMPED "PEARSON HILL
 1962 1950.447" AND TAGGED WITH A STANDARD BM MARKER. (ELEV. BY USGS)

LINE 4

BOOK CV-1470 1962 F. W. KRUEGER

218 - RIB LAKE

BM OGEMA TOWER 1934 0 0 00.4 595.335 M 1953.195 FI
 BM, NGS TRIANGULATION STATION OGEMA, ABOUT 5 MI E. OF; IN NW 1/4
 NW 1/4 SEC. 11, T. 34 N., R. 2 E., ON WOODEN PROMINENT KNOWN LOCALLY
 AS TIMMS HILL, CENTER UNDER 84 FT STEEL TOWER, IN CONCRETE POST;
 STANDARD TABLET STAMPED "OGEMA TOWER 1934 1952.868" THIS MARK PRO-

LINE 0

BOOK CV-3214 1975 W. R. MCFARLIN

218 - RIB LAKE

- MP 20 FWK 1 1 48 00.8 524.041 M 1719.290 FT
MP, NEAR COR. SECS. 3, 4, 9 AND 10, T. 34 N., R. 2 E.; 31 FT S. AND 10 FT E. AND 0.05 FT LOWER THAN CENTER OF HWY. 86 AT PRIVATE DRIVE S., ON TOP OF A 2 FT METAL CULVERT; A PUNCHED HOLE
- MP 20 FWK 2 1 50 01.6 527.010 M 1729.030 FT
MP, NEAR QUARTER COR. BETWEEN SECS. 2 AND 3, T. 34 N., R. 2 E.; 55 FT N. AND 12.8 FT LOWER THAN CENTER OF HWY. 86 AT CULVERT, ON TOP OF N. END OF A 2 FT METAL CULVERT; A PUNCHED HOLE
- MP 20 FWK 3 1 52 02.4 545.746 M 1790.500 FT
MP, IN SE 1/4 SEC. 2, T. 34 N., R. 2 E.; 56 FT S. AND 130 FT E. AND 5.7 FT LOWER THAN CENTER OF HWY. 86 AT T-RD. S., ON TOP OF A 2 FT METAL CULVERT; A PUNCHED HOLE
- MP 3 WRM 1975 RM 1 54 03.5 543.213 M 1782.190 FT
REFERENCE MARK, 97 FT S. AND 31 FT E. FROM CENTER OF HWY. 86 AT T-RD. S., 48 FT N. AND 12 FT W. OF BM 3 WRM, IN W. BASE OF A 24 IN. YELLOW BIRCH TREE; A RR. SPIKE
- BM 3 WRM 1975 1 55 03.5 544.353 M 1785.930 FT
BM, SPIRIT PRICE CO., 3 MI W. OF; NEAR QUARTER COR. BETWEEN SECS. 1 AND 12, T. 34 N., R. 2 E.; 145 FT S. AND 43 FT E. AND 8.7 FT HIGHER THAN CENTER OF HWY. 86 AT T-RD. S., 2 FT N. OF A METAL WITNESS POST; SET ON A COPPER COATED STEEL ROD AND INSIDE A 4 IN. TILE, SET FLUSH WITH THE GROUND; A STANDARD TABLET STAMPED "3 WRM 1975"
- MP 3 WRM A 1 58 04.5 529.436 M 1736.990 FT
MP, NEAR QUARTER COR. BETWEEN SECS. 6 AND 7, T. 34 N., R. 3 E.; 32 FT S. AND 16 FT W. AND 0.3 FT LOWER THAN CENTER OF HWY. 86 AT T-RD. S., ON W. END OF A 2 FT METAL CULVERT; A PUNCHED HOLE
- MP 3 WRM B 1 60 05.4 504.332 M 1654.630 FT
MP, NEAR QUARTER COR. BETWEEN SECS. 5 AND 8, T. 34 N., R. 3 E.; 20 FT S. AND 2.8 FT LOWER THAN CENTER OF HWY. 86 AT CULVERT OVER W. FORK SPIRIT RIVER, ON TOP OF S. END OF THE W. METAL CULVERT; PUNCHED HOLE
- MP 3 WRM C 1 62 06.1 512.193 M 1680.420 FT
MP, NEAR COR. SECS. 4, 5, 8 AND 9, T. 34 N., R. 3 E.; 22 FT S. AND 13 FT E. AND 0.8 FT LOWER THAN CENTER OF HWY. 86 AT CROSSROADS, ON TOP OF E. END OF A 2 FT METAL CULVERT; A PUNCHED HOLE
- UE 4 WRM RM 1 64 06.4 515.988 M 1692.870 FT
REFERENCE MARK, 54 FT S. AND 16 FT E. FROM CENTER OF HWY. 86 AT W. DRIVE INTO CHURCH S., 23 FT N. OF BM 4 WRM, ON NW. COR. OF W. SIDEWALK INTO CHURCH; A CHISELED SQUARE
- BM 4 WRM 1975 1 65 06.4 516.496 M 1694.538 FT
BM, 0.5 MI W. OF SPIRIT, PRICE CO., NEAR W. SIXTEENTH COR. BETWEEN SECS. 4 AND 9, T. 34 N., R. 3 E.; 54 FT S. AND 39 FT E. FROM CENTER OF HWY. 86 AT W. DRIVE INTO CHURCH S., ON TOP OF STEP OF N. ENTRANCE INTO SPIRIT BAPTIST CHURCH, SET IN A DRILL HOLE; A STANDARD TABLET STAMPED "4 WRM 1975"

MP 4 WRM A 1 07 07.2 494.128 M 1621.150 FI
 MP, NEAR COR. SECS. 3, 4, 9 AND 10, T. 34 N., R. 3 E.; 23 FT N. AND
 4.3 FT LOWER THAN CENTER OF HWY. 86 AT CULVERT OVER MARHEIME CREEK, ON
 TOP OF N. END OF W. METAL CULVERT; A PUNCHED HOLE

BM CEMETERY NO 2 1952 RM 1 69 08.0 499.338 M 1638.245 FI
 REFERENCE MARK, 70 FT SW. OF MAIN STATION, 25 FT S. OF CENTER OF
 HWY. 86, A STANDARD DISK IN A CONCRETE MONUMENT PROJECTING 2 IN.
 STAMPED "CEMETERY NO 2 1952"

BM CEMETERY NO 1 1952 RM 1 70 08.0 497.937 M 1633.648 FI
 REFERENCE MARK, 87 FT E. OF MAIN STATION, 25 FT N. OF CENTER OF HWY.
 86, 5 FT S. OF A OAK TREE; A STANDARD DISK, IN A CONCRETE MONUMENT,
 PROJECTING 4 IN. STAMPED "CEMETERY NO. 1 1952"

BM CEMETERY 1952 1 71 08.0 498.624 M 1635.903 FI
 BM, NGS TRIANGULATION STATION, STATION IS LOCATED ABOUT 17 MI W. OF
 TUMAHAWK, 11 MI SE. OF PRENTICE, 1.25 MI E. OF JUNCTION OF STATE HWY.
 86 AND STATE HWY. 102, IN SEC. 3, T. 34 N., R. 3 E.; TO REACH THE
 STATION FROM THE JUNCTION OF U.S. HWY. 51 AND STATE HWY. 86 IN
 TUMAHAWK, GO S. THEN W. ON STATE HWY. 86 FOR 13.5 MI TO THE SCHOOL
 HOUSE IN THE VILLAGE OF SPIRIT FALLS, CONTINUE W. ON STATE HWY. 86,
 4.9 MI TO THE DRIVEWAY TO CHRIS LONG'S FARM HOUSE ON THE RIGHT, CON-
 TINUE W. ON STATE HWY. 86 FROM 0.45 MI TO THE GATE INTO A CEMETERY, ON
 THE RIGHT AND THE STATION, 37 YDS. E. OF THE GATE; A STANDARD DISK
 SET IN A CONCRETE MONUMENT STAMPED "CEMETERY 1952"

BM CEMETERY AZ MK 1952 1 73 08.5 488.547 M 1602.842 FI
 BM, 0.4 MI E. OF MAIN STATION; 50 FT N. AND 12 FT W. OF HWY. 86 AND
 T-RD. N., SET FLUSH WITH THE GROUND, A STANDARD DISK STAMPED "CEMETERY
 1952"

MP AZIMUTH A 1 75 09.6 476.437 M 1563.110 FI
 MP, NEAR QUARTER COR. BETWEEN SECS. 1 AND 12; T. 34 N., R. 3 E.; 18 FT
 N. AND 1.5 FT LOWER THAN CENTER OF HWY. 86 AT CULVERT, ON TOP OF N.
 END OF A 2 FT METAL CULVERT; PUNCHED HOLE

UE 15 DNB 1970 RM 1 76 10.5 470.042 M 1542.130 FI
 REFERENCE MARK, 100 FT NW. OF MARK, ON TOP OF NW. WINGWALL; A CHISELED
 CROSS

LINE 7

BOOK CV-3214 1975 W. R. MCFARLIN 218 - RIB LAKE

MP 15 DNB 1 2 4 01.4 461.910 M 1515.470 FI
 MP, NEAR W. SIXTEENTH CURS. BETWEEN SECS. 13 AND 18, T. 34 N., RS. 3
 AND 4 E.; 31 FT W. AND 1.3 FT LOWER THAN CENTER OF RD. AT CULVERT OVER
 MARHEIME CREEK, ON TOP OF NORTHERLY 6 FT METAL CULVERT; A PUNCHED HOLE

MP 15 DNB 2 2 6 02.2 465.565 M 1527.440 FI
 MP, NEAR COR. SECS. 13, 16, 19 AND 24, T. 34 N., RS. 3 AND 4 E.;
 69 FT W. AND 4.1 FT HIGHER THAN CENTER OF RD. AT DRIVE E., IN E. BASE
 OF A 3 FT ELM TREE; A RR. SPIKE

MP 15 D&B 3 2 8 03.2 459.536 M 1507.660 FT
 MP, NEAR CENTER OF SEC. 24, T. 34 N., R. 3 E.; 19 FT W. AND 2.7 FT
 LOWER THAN CENTER OF RD. AT CULVERT, ON TOP OF N. END OF A METAL CUL-
 VERT OVER TRIN CREEK; A PUNCHED HOLE

MP 5 WRM RM 2 10 03.9 460.749 M 1511.640 FT
 REFERENCE MARK, 29 FT S. AND 106 FT E. OF T-RD. S., 46 FT S. AND 67 FT
 E. OF BM 5 WRM IN W. BASE OF A 14 IN. POPLAR TREE; A RR. SPIKE

BM 5 WRM 1975 2 11 03.9 461.535 M 1514.219 FT
 BM, RIB LAKE, TAYLOR CO., 6.5 MI W. AND 7 MI E. OF; IN PRICE CO., NEAR
 CUR. SECS. 23, 24, 25 AND 26, T. 34 N., R. 3 E.; 40 FT W. AND 19 FT
 E. AND 2.3 FT HIGHER THAN CENTER OF CU. RD. "YY" AND MEIR RD. S., 1
 FT S. OF A METAL WITNESS POST, ON A COPPER COATED STEEL ROD AND INSIDE
 A 4 IN. TILE; STANDARD TABLET STAMPED "5 WRM 1975"

MP 5 WRM A 2 14 05.0 484.158 M 1588.440 FT
 MP, NEAR COR. SECS. 25, 26, 35 AND 36, T. 34 N., R. 3 E.; 70 FT S. AND
 40 FT W. AND 4.7 FT HIGHER THAN CENTER OF CROSSROADS, IN N. BASE OF A
 32 IN. MAPLE TREE; A RR. SPIKE

UE 5 WRM B 2 17 06.1 502.793 M 1649.560 FT
 UE, NEAR W. SIXTEENTH CUR. BETWEEN SECS. 1 AND 36, TSP. 33 AND 34 N.,
 R. 3 E.; 115 FT NE. AND 2.5 FT LOWER THAN CENTER OF T-RD. S., NEAR
 HIGH POINT OF A 4 X 6 GRANITE ROCK; A CHISELED SQUARE

UE 5 WRM C 2 20 07.2 485.797 M 1593.820 FT
 UL, IN SE 1/4 SEC. 1, T. 33 N., R. 3 E.; 7 FT W. AND 0.3 FT LOWER THAN
 CENTER OF RD. AT CULVERT ON TOP OF W. END OF A CONCRETE TUBE TYPE CUL-
 VERT; A CHISELED SQUARE

MP 6 WRM RM 2 22 07.8 491.250 M 1611.710 FT
 REFERENCE MARK, 25 FT N. AND 26 FT E. FROM CENTER OF RD. AT CREST, 51
 FT E. OF BM 6 WRM IN W. BASE OF A 10 IN. POPLAR TREE; A RR. SPIKE

BM 6 WRM 1975 2 23 07.8 492.240 M 1614.957 FT
 BM, RIB LAKE, TAYLOR CO., 3 MI W. AND 7.5 MI E. OF; NEAR CENTER OF
 SEC. 12, T. 33 N., R. 3 E.; ABOUT 200 FT W. OF N. END OF A CURVE IN
 RD., 25 FT W. AND 25 FT W., 16 FT HIGHER THAN RD. AT CREST, 1 FT E.
 OF METAL WITNESS POST, ON A COPPER COATED STEEL ROD AND INSIDE A 4 IN.
 TILE; STANDARD TABLET STAMPED "6 WRM 1975"

MP 6 WRM A 2 26 08.9 499.925 M 1640.170 FT
 MP, IN NE 1/4 SEC. 13, T. 33 N., R. 3 E.; 5 FT S. AND 119 FT E. AND
 0.2 FT HIGHER THAN CENTER OF RD. AT TRAIL E., IN W. BASE OF A 10 IN.
 CHERRY TREE; A RR. SPIKE

MP IT 54 B RM 2 29 09.8 499.943 M 1640.230 FT
 REFERENCE MARK, 22 FT S. AND 12 FT E. FROM CENTER OF Y-RDS., 3 FT S.
 AND 16 FT E. OF BM IT 54 B, IN SW. BASE OF A 5 IN. WHITE BIRCH TREE; A
 RR. SPIKE

BM IT 54 B 1947 2 30 09.8 500.101 M 1640.748 FT
 BM, RIB LAKE, TAYLOR CO., 1.4 MI W. AND 7.5 MI E. OF; IN NW. COR. SEC.
 24, T. 33 N., R. 3 E.; 19 FT S. AND 6 FT W. AND 1.1 FT HIGHER THAN

